


# Advanced Modelica Tutorial

Hilding Elmqvist, Dynasim

Hans Olsson, Dynasim

Martin Otter, DLR

Modelica 2002, March 18-19, DLR Oberpfaffenhofen



# Contents

- Initialization
- Enumerations
- Control of state selection
- Improved Component Arrays
- Reduction operators
- Replaceable components, Replaceable packages
- Record constructor and datasheet libraries
- Extended function call + scripting
- External Utility functions; ModelicaError etc.
- External Objects

# Initialization

Flexible specification of initial conditions as well as the correct solution of difficult, non-standard initialization problems occurring in industrial applications, for example:

- Stationary initialization around a constant reference velocity of an aircraft.
- Stationary initialization around periodic solutions, needed in power systems or in detailed engine models.
- Stationary initialization of continuous systems controlled by sampled data systems (the states of the discrete controllers are computed in such a way that the overall system is in a steady state when simulation starts).
- Initialization of discontinuous or variable structure systems, e.g., systems containing friction or backlash.

## DAE formulation

$$F(t, \mathbf{x}, \frac{d\mathbf{x}}{dt}, \mathbf{w}) = 0$$

After index reduction

$$G(t, \mathbf{x}_1, \frac{d\mathbf{x}_1}{dt}, \mathbf{x}_2, \text{der\_}\mathbf{x}_2, \mathbf{w}_1, \mathbf{w}_2, \text{der\_}\mathbf{w}_2) = 0$$

ODE formulation (locally)

$$\left(\frac{d\mathbf{x}_1}{dt}, \mathbf{x}_2, \text{der\_}\mathbf{x}_2, \mathbf{w}_1, \mathbf{w}_2, \text{der\_}\mathbf{w}_2\right) = \mathbf{f}(t, \mathbf{x}_1)$$

Dynamic state ( $\mathbf{x}_1$ ) selection

## Initial conditions

At initial time, solve index-one DAE equations for all variables except  $t_0$

$$G(t_0, x_1(t_0), \frac{dx_1}{dt}(t_0), x_2(t_0), \text{der\_}x_2(t_0), w_1(t_0), w_2(t_0), \text{der\_}w_2(t_0)) = 0$$

$\dim(x_1)$  more equations needed

## The start and fixed attributes

- `Real v(start=expr, fixed=true);`  
`// v(t0) = expr(t0);`
- **Steady-state initialization:**  
`Real der_v(start=0, fixed=true) = der(v);`  
`// dv/dt(t0) = 0;`
- **General initialization equation (residue):**  
`Real ic(start=0, fixed=true) = expr1 - expr2;`  
`// expr1(t0) = expr2(t0);`

## NEW: initial equation

- **initial equation**

```
v = expr;
```

```
// v(t0) = expr(t0);
```

- Steady-state initialization:

**initial equation**

```
der(v) = expr;
```

```
// dv/dt(t0) = expr(t0);
```

- General initialization equation (residue):

**initial equation**


```
expr1 = expr2;
```

```
// expr1(t0) = expr2(t0);
```

```
pre(x) = x; // Steady-state for discrete variable
```

## Pendulum example

```
• model Pendulum
  parameter Real g = 9.81;
  parameter Real m = 1;
  parameter Real L = 1;
  Real phi, w;
equation
  der(phi) = w;
  m*der(w) = -(m*g/L)*sin(phi);
end Pendulum;
```



- Warning: The initial conditions for variables of type Real are not fully specified. There are 2 scalar conditions missing. Assuming default start values for:  
phi(start = 0)  
w(start = 0)

## Pendulum initialization (1)

- Initialize angle and angular velocity

```
model PendulumInitialization1
  extends Pendulum(
    phi(start=1, fixed=true),
    w  (start=0, fixed=true)
  );
end PendulumInitialization1;
```

- Equivalent:


```
model PendulumInitialization2
  extends Pendulum;
initial equation
  phi=1;
  w=0;
end PendulumInitialization2;
```

## Pendulum initialization (2)

- Alternative - cartesian initial values:

```
model PendulumInitialization3
  extends Pendulum;
  Real x(start=L); // approximate value
  Real y; // (start = 0, fixed = true);
equation
  x = L*sin(phi);
  y = -L*cos(phi);
initial equation
  y=0;
  der(y)=0;
end PendulumInitialization3;
```

*differentiated*



- Nonlinear system of equation  $0 = -L \cdot \cos(\phi)$  solved for  $\phi$
- Linear equation for  $w$ :  $\mathbf{der}(\phi) = \mathbf{der}(y) / (L \cdot \sin(\phi))$

## Pendulum initialization (3)

- Alternative - cartesian initial values:

```
model PendulumInitialization4
  extends Pendulum;
  Real x, y;
equation
  x = L*sin(phi);  y = -L*cos(phi);
initial equation
  der(x)=1;
  der(y)=2;
end PendulumInitialization4;
```

- Nonlinear system of equations

$0 = \text{der}(x) - L \cdot \text{der}(\text{phi}) \cdot \cos(\text{phi}); \quad 0 = \text{der}(y) - L \cdot \text{der}(\text{phi}) \cdot \sin(\text{phi})$   
solved for phi and **der(phi)**

## Pendulum initialization (4)

- Alternative - cartesian initial values:

```
model PendulumInitialization5
  extends Pendulum(L(fixed=false));
  Real x, y;
equation
  x = L*sin(phi);  y = -L*cos(phi);
initial equation
  x=1;  y=2;  w=0;
end PendulumInitialization5;
```

- Nonlinear system of equations

```
x = L*sin(phi);  y = -L*cos(phi);
```

solved for phi and L

## Initialization of discrete models

- For discrete variables declarations

```
Real    x(start = 10,    fixed = true);
```

```
Boolean b(start = false, fixed = true);
```

```
Integer i(start = 1,    fixed = true);
```

imply the additional initialization equations

```
pre(x) = 10;
```

```
pre(b) = false;
```

```
pre(i) = 1;
```

- Needed for discrete systems or difference equations (when **pre(v)** appear)
- The value of variables assigned in when clauses before the first sampling

## Initialization of difference equations

- Steady state initialization:

```
Real x;
```

```
equation
```

```
when { initial (), sample (1, 10) } then
```

```
  x = a*pre(x) + b*u;
```

```
end when;
```

```
initial equation
```

```
  pre(x) = x;
```

Difference equation also valid initially

- Assume  $u(t_0)$  given
- Solution:

```
pre(x) := b*u(t0) / (1-a);
```

```
x := pre(x);
```

## Continuous and discrete initialization

```
Real          x;
discrete Real xd;
discrete Real u;
parameter Real k=10, T=1;
parameter Real Ts = 0.01 "Sample time";
input      Real xref "reference input";
equation
// Plant model
der(x) = -x + u;
// Discrete PID controller
when { initial() , sample(0, Ts) } then
  xd = pre(xd) + Ts/T*(x - xref);
  u = k*(xd + x - xref);
end when;
initial equation
  der(x) = 0;
  pre(xd) = xd;
```

## Continuous and discrete initialization (2)

- The initialization problem becomes

```
der (x) := 0
// Linear system of equations in the
// unknowns: xd, pre(xd), u, x
pre (xd) = xd
xd       = pre (xd) + Ts/T* (x - xref)
u        = k*(xd + xref - x)
der (x)  = -x + u;
```

- Solving the system of equations gives

```
der (x) := 0
x      := xref
u      := xref
xd     := xref/k
pre (xd) := xd
```

# Enumerations

- New user defined base data types
- Ordered set of values with unique identifiers
- **type** TextStyle = **enumeration**(Bold, Italic, UnderLine);
- TextStyle t1 = TextStyle.Bold;
- TextStyle t2 = t1;
- Operations: <, <=, >, >=, ==, <>
- Future - arrays over enumerations:
- Boolean textStyles[TextStyle] = {false, false, true};
- textStyles[TextStyle.Bold] := true;

# State Variable Selection

- DAE:  
 $\mathbf{0} = \mathbf{f}(\mathbf{dx}/dt, \mathbf{x}, \mathbf{y}, t)$
- After index reduction conceptually transformed to ODE (locally):  
$$\mathbf{dx}_s/dt = \mathbf{f}_1(\mathbf{x}_s, t)$$
$$\mathbf{x}_n = \mathbf{f}_2(\mathbf{x}_s, t)$$
$$\mathbf{y} = \mathbf{f}_3(\mathbf{x}_s, t)$$
- $\mathbf{x}_s$ : states,  $\mathbf{x}_n$ : non-states
- Selection of states can almost always be done automatically
- Selection might need to be done dynamically along the trajectory

## Manual State Selection

Reasons for manual state selection:

- Accuracy - relative coordinates
- Efficiency by avoiding inverting functions - e.g. thermodynamic properties
- Selecting a less nonlinear representation - e.g. Park transformation
- Avoiding dynamic state selection - mechanical systems
- Sensors - variables not states

## State Selection Control

- **type** StateSelect = **enumeration** (  
never, avoid, default, prefer, always);
- stateSelect - new attribute of Real variables
- Real w(stateSelect = StateSelect.prefer);
  - *never*: Do not use as a state at all.
  - *avoid*: Avoid it as state in favour of those having the *default value*
  - *default*: If the variable does not appear differentiated in the model this means *never*.
  - *prefer*: Prefer it as state over those having the *default value*.
  - *always*: Do use it as a state.

# Component arrays

- Basic idea of additions:
  - Make Modelica.Blocks user-friendly
    - Vectorization handled by translator not by user-models
  - Make blocks in Modelica.Blocks easy to write
    - Text-book models
    - More components
  - Support component arrays
  - Clearly defined language

## Component arrays [old Modelica.Blocks.Sources.Sine]

```
block Sine "Generate sine signals"
  parameter Real amplitude[:]={1} "Amplitudes of sine waves";
  parameter SIunits.Frequency freqHz[:]={1} "Frequencies of sine waves";
  parameter SIunits.Angle phase[:]={0} "Phases of sine waves";
  parameter Real offset[:]={0} "Offsets of output signals";
  parameter SIunits.Time startTime[:]={0} "Output = offset for time < startTime";
  extends Interfaces.MO(final nout=max([size(amplitude, 1); size(freqHz, 1);
    size(phase, 1); size(offset, 1); size(startTime, 1)]));
protected
  constant Real pi=Modelica.Constants.PI;
  parameter Real p_amplitude[nout]=(if size(amplitude, 1) == 1 then ones(nout)*
amplitude[1] else amplitude);
  parameter Real p_freqHz[nout]=(if size(freqHz, 1) == 1 then ones(nout)*freqHz[1] else
freqHz);
  parameter Real p_phase[nout]=(if size(phase, 1) == 1 then ones(nout)*phase[1] else
phase);
  parameter Real p_offset[nout]=(if size(offset, 1) == 1 then ones(nout)*offset [1] else
offset);
  parameter SIunits.Time p_startTime[nout]=(if size(startTime, 1) == 1 then
ones(nout)*startTime[1] else startTime);
equation
  for i in 1:nout loop
    outPort.signal[i] = p_offset[i] + (if time < p_startTime[i] then 0 else
      p_amplitude[i]*Modelica.Math.sin(2*pi*p_freqHz[i]*(time - p_startTime[i])
      + p_phase[i]));
  end for;
end Sine;
```

## Component arrays [new Modelica.Blocks.Sources.Sine]

```
block Sine "Generate sine signal"  
  parameter Real          amplitude=1;  
  parameter SIunits.Frequency freqHz=1;  
  parameter SIunits.Angle   phase=0;  
  parameter Real          offset=0;  
  parameter SIunits.Time    startTime=0  
  "Output = offset for time < startTime";  
  extends Interfaces.SO;  
equation  
  y = offset + (if time < startTime then 0 else  
    amplitude*Modelica.Math.sin(  
      2* Modelica.Constants.pi *  
      freqHz*(time-startTime)+ phase));  
end Sine;
```

## Component arrays [connectors]

```
connector InPortNew = input Real annotation(...);
```

Advantages:

- Drag-and-drop of real-valued connector
- Remove size-parameter
- Avoid `.signal[1]`
- Already existing `u, y` in Interfaces

## Component arrays [use of library]

```
Sine base[3];  
Sine source[3](each frequency=50,  
              phase = {0, 2, -2});
```

```
block CrossProduct  
  extends MI2MO(final n=3);  
equation  
  y = cross(u1, u2);  
end CrossProduct;  
CrossProduct a;
```

```
equation  
connect(source.y, a.u1);  
connect(base.y,   a.u2);
```

# Iterators

- Reduction Operators: sum, product, min, max
  - `sum(u[i]*v[i]^2 for i in 1:size(u,1))`
- Array construction
  - `{u[i]^2 for i in 1:size(u,1)}`
- Deduction of Ranges
  - `for i loop A[i] = B[i]^2; end for;`
  - `sum(u[i]*v[i]^2 for i)`
- Using **end** as array index
  - `v[end-1]=u[end];`

# Replaceable / redeclare

Very minor additions in Modelica 2

## Contents


- Replaceable component
- Replaceable model
- Replaceable package
  - Medium models

# Replaceable component

- Redeclare **component** model
- Individually change model
- Keep connections and parameters
- Checking for consistency


```

model C
  replaceable GreenModel comp1 (p1=5);
  replaceable YellowModel comp2;
  replaceable GreenModel comp3;
  connect (...);
end C;
  
```



```


model C2 =
  C (redeclare RedModel comp1,
    redeclare GreenModel comp2);
  
```



Equivalent to

```

model C
  RedModel comp1 (p1=5);
  GreenModel comp2;
  GreenModel comp3;
  connect (...);
end C;
  
```




## Example - redeclare component model

```
model MotorDrive
  replaceable PI controller;
  Motor      motor;
  Gearbox    gearbox (n=100);
  Shaft      J1 (J=10);
  Tachometer wl;

equation
  connect (controller.out, motor.inp);
  connect (motor.flange   , gearbox.a);
  connect (gearbox.b      , J1.a);
  connect (J1.b           , wl.a);
  connect (wl.w           , controller.inp);
end MotorDrive;

model MotorDrive2 = MotorDrive
  (redeclare AutoTuningPI controller);
```





## Replaceable model

- Redeclare **model**
- replace the model of many components


```
class C
  replaceable model ColouredClass = GreenClass;
  ColouredClass comp1(p1=5);
  replaceable YellowClass comp2;
  ColouredClass comp3;
  connect(...);
end C;
```

```
class C2 =
  C(redeclare model ColouredClass = BlueClass);
```



Equivalent to

```
class C
  BlueClass comp1(p1=5);
  YellowClass comp2;
  BlueClass comp3;
  connect(...);
end C;
```



## Modifying packages

```
package FixedSampler=Modelica.Blocks.Discrete(  
  redeclare model Sampler=...);
```

- Useful when:
  - All models depend on the same base-model
- Useful for:
  - Different sampler
  - Different fidelity
  - Difference in a *single* model

# Replaceable packages

[courtesy of Mike Tiller, Ford]

- Consistent set of
  - models
  - connectors
  - utility functions
  - constants
- When replaceable model does not suffice:
  - Medium model
  - Heat-transfer property

## What is a Medium Model?

- Material properties
  - Enthalpy, Energy
  - Viscosity
- Chemical representations (# of species)
- Chemistry (e.g. kinetics, combustion)
- Functions
  - AFR, Equivalence ratio, Ambient conditions

## Key Points

- Reusability
  - Develop a single component model
- Variable Fidelity
  - Substitute different physics
- Conflicting requirements?

## Design of an Engine

- Manifold (manifold volume)
- Throttle (throttle diameter)
- Engine block (inertia)
  - Engine Cylinders (quantity)
    - Engine Valves (diameters)
    - Combustion Chamber (bore, stroke, ...)
  - Crankshaft (crank, connecting rod)
  - Engine Mount (stiffness)

## Medium Components

- **Manifold** (manifold volume)
- **Throttle** (throttle diameter)
- Engine block (inertia)
  - Engine Cylinders
    - **Engine Valves** (diameters)
    - **Combustion Chamber** (bore, stroke, ...)
  - Crankshaft (crank, connecting rod)
  - Engine Mount (stiffness)

## Changing Medium Models

- “Flip of a switch”.
- Should not have to replace existing component models (not changing physical design)
- Should not be a burden on the model developers to maintain different fundamental components.

## What is a Medium Model?

- Consistent set of
  - Models
  - Functions
  - Constants
  - Connectors
- Usage is on demand
  - Well organized
  - Computationally efficient

## Modelica Implementation

- Modelica has great features to support this approach:
  - Packages
  - Partial definitions
  - Replaceable+Redeclare

## Using Packages

- Consistent set of types.
- Partial package definition includes:
  - Property model
  - Number of species (constant)
  - Connectors
  - Utility functions

## Package definition

```
within Ford.Thermodynamics;  
partial package MediumModel  
  constant Integer nspecies;  
  model PropertyModel ... end PropertyModel;  
  connector MediumFlow ... end MediumFlow;  
  function AirFuelRatio ... end AirFuelRatio;  
  ...  
end MediumModel;
```

## Medium Component

```
within Ford.Thermodynamics;  
model MediumComponent  
  replaceable package MediumModel  
    =Ford.Thermodynamics.MediumModel;  
end MediumComponent;  
  
model Pump  
  extends MediumComponent;  
  MediumModel.MediumFlow flow_a;  
  MediumModel.MediumFlow flow_b;  
equation  
  for i in MediumModel.nspecies loop ... end for;  
end Pump;
```

# Diagrams

```
model subsystem
  extends MediumComponent;
  Pump p1(redeclare package
    MediumModel=MediumModel);
  Valve v1(redeclare package
    MediumModel=MediumModel);
equation
  connect(p1.flow_a, v1.flow_b);
  ...
end subsystem;
```

## Top Level

```
model Engine=Ford.Engines.V6(redeclare package  
MediumModel=Ford.Media.PerfectGas);
```

## Positional *and* Named Arguments in Functions

```
function RealToString  
  input   Real number;  
  input   Real precision = 6;  
  input   Real minLength = 0;  
  ...  
end RealToString;
```

Modelica 1.4:

```
RealToString(number = 2.0);  
RealToString(2.0, 6, 0);
```

Added in Modelica 2.0:

```
RealToString(2.0);  
RealToString(2.0, 6);  
RealToString(2.0, precision=6);  
RealToString(2.0, minLength=0);
```

## Benefits of mixed arguments

- Possible to extend a function with new optional arguments
  - *Must have default values for extra argument*
  - Existing use not influenced
  - As adding extra parameters to model
  - Replaceable functions
- Same function for experts and novice users
  - Easier to find them
  - Various expert options with reasonable defaults
  - Easier maintenance

## Optional outputs [Example]

```
function eigen
  parameter Integer n = size(A,1);
  input Real A[:,n];
  input Boolean getREV = false;
  input Boolean getLEV = false;
  output Real eigenValues[n,2];
  output Real REV[n,n] (enable=getREV);
  output Real LEV[n,n] (enable=getLEV);
  ...
end eigen;

ev = eigen(A);
b = isStable(eigen(A));
(ev, REV) = eigen(A, getREV=true);
(ev, REV, LEV) = eigen(A, getREV=true,
                       getLEV=true);
```

## Optional outputs

- Enable-attribute of outputs
  - Default is enable=true
  - Given directly by inputs
- Explicitly use enable-attribute since:
  - Type safe
  - Understandable results
  - Experience from Matlab

## Scripting/Interactive use of functions

- Modelica syntax:
- Can call:
  - Modelica functions
  - external functions
- Use for:
  - Post-processing
  - Understanding Modelica functions
- Will benefit from large function library (under development)

```
A = sum(B[:,k,:] for k);
```

```
ev = eigen(A);
```

```
(ev, REV, LEV) = eigen(A, getREV=true, getLEV=true);
```

```
eigen(A, getREV=true, getLEV=true);
```

## Record constructor

```
record Complex "Complex number"  
  Real re "real part";  
  Real im "imaginary part";  
end Complex;  
  
function Complex "Automatically generated"  
  input Real re "real part";  
  input Real im "imaginary part";  
  output Complex out(re=re, im=im);  
end Complex;  
  
function add "Add Comp. numbers"  
  input Complex u, v;  
  output Complex w(re=u.re + v.re, im= u.im +  
v.im);  
end add;  
  
Complex c1;  
Complex c2 = add(c1, Complex(sin(time), cos(time)));
```

## Data sheet libraries [using record constructor]

```
record MotorData
  parameter Real inertia;
  parameter Real nominalTorque;
  parameter Real maxTorque;
  parameter Real maxSpeed;
  ...
end MotorData;

model Motor
  MotorData data;
  // connector definitions
equation
  ...
end Motor;
```

When using a motor, specific values of the motor data could be given in the usual way:

```
model Robot1
  Motor m1(data(inertia      = 0.001,
                 nominalTorque = 10,
                 maxTorque    = 20,
                 maxSpeed     = 3600));
  Motor m2(data(...));
  ...
end Robot1;
```

When using the same motor type several times, it is better to define the motor data just ones, i.e., build up a **data sheet library** by **modifications** of the default values of the basic MotorData record


```

package Motors
  record M103 = MotorData(
    inertia          = 0.001,
    nominalTorque    = 10,
    maxTorque        = 20,
    maxSpeed         = 3600);

  record M103a = M103(maxTorque=12);
  ...
end Motors;

model Robot2
  Motor m1(data = Motors.M103());
  Motor m2(data = Motors.M103a(
    inertia=0.0012));
  ...
end Robot2;

```

record constructor  


## External Utility Functions

- `char* ModelicaAllocateString(size_t len)`
  - Return strings from external routines
  - Variant for error handling
- `void ModelicaError(const char* string)`
  - “Assert“ in external routines
  - Variant for format control of message
- `void ModelicaMessage(const char* string)`
  - Information messages from external routines
  - Variant for format control of message

## External Utility Functions [Example]

### Modelica:

```
function blanks "Creates string with n blanks"  
  input Integer n(min=0);  
  output String blankString;  
  external "C"  
end blanks;
```

### C:

```
#include "ModelicaUtilities.h"  
const char* blanks(int n) {  
  /* Create string with n blanks */  
  char *c = ModelicaAllocateString(n);  
  int i;  
  for(i=0; i<n; ++i) c[i]=' '  
  c[n]='\0';  
  return c;  
}
```

# External Objects

```
class MyTable
  extends ExternalObject;

  function constructor
    input String fileName;
    input String tableName;
    output MyTable table;
    external "C";
  end constructor;

  function destructor
    input MyTable table;
    external "C";
  end destructor;
end MyTable;
```

## External Objects [Example: Declaration continued]

```
function interpolateMyTable  
  input MyTable table;  
  input Real u;  
  output Real y;  
  external "C";  
end interpolateMyTable;
```

## External Object [Example: Use]

```
model test
  MyTable table1("testTables.txt", "table1");
  input Real u1;
  output Real y1;
equation
  y1 = interpolateMyTable(table1, u1);
end test;
```

## External Object [Example: C-implementation]

```
typedef struct {  
    double* array;  
    int      nrow;  
    int      ncol;  
    int      type; /* interpolation type */  
    int      lastIndex; /* for search */  
} MyTable;  
  
void* initMyTable(const char* fileName,  
                  const char* tableName) {  
    MyTable* table=malloc(sizeof(MyTable));  
    if (!table) ModelicaError("Not enough memory");  
    // read table from file and store data in *table  
    return (void*) table;  
}
```

## External Object [Example: C-implementation]

```
void closeMyTable(void* object) {  
    MyTable* table = (MyTable*) object;  
    free(table->array);  
    free(table);  
}
```

```
double interpolateMyTable(void* object, double u) {  
    MyTable* table = (MyTable*) object;  
    double y;  
    // Interpolate using "*table" data  
    return y;  
}
```

## Use of External Objects

- Special data-structures
  - User-defined table data structures
  - Access to external databases for properties
  - Handling of special matrices, e.g. sparse
- Hardware interfaces, since the constructor and destructor are called exactly once, even in case of errors

## Try to avoid using External Objects (if straightforward)!

- How:
  - Convert property data into Modelica
    - Data-sheet libraries
  - Use one external Routine for reading data into Modelica table
  - Table-interpolation in Modelica (state-less with binary search)
    - Might be less efficient
- Why:
  - Better support for unexpected re-use
  - Better support for code modification
  - Interactive use
  - Not a black box

# What is implemented of Modelica 2.0 in Dymola 4.2a?

- Initialization
- State-select-attribute
- Translator for component arrays (each, connect, etc)
- Replaceable component/model/function/package
- Scripts
- Array indexing with **end**
  
- Almost implemented:
  - Utility functions
  - Iterators
  - Mixed positional and named arguments

